



所有尺寸：毫米

公制螺纹	螺纹规格	规格型号		螺纹代码	尾缀代码	最小板厚	板开口尺寸 +0.08	C Max.	D Max.	E Max.	T Max.	孔中心到板边缘的最小距离	安装下模沉孔直径 Max.
		螺母材料											
		碳钢	不锈钢										
	M3x0.5	PL	PLC	M3	1.53	1.53-1.78	6.0	5.98	5.52	7.01	3.56	4.32	3.5
	M4x0.7	PL	PLC	M4	1.53	1.53-1.78	7.5	7.48	7.01	8.54	4.2	5.59	4.5
	M5x0.8	PL	PLC	M5	1.53	1.53-1.78	8.0	7.98	7.52	9.0	4.45	6.35	5.5

所有尺寸：英寸

英制螺纹	螺纹规格	规格型号		螺纹代码	尾缀代码	最小板厚	板开口尺寸 +.003 -.000	C Max.	D Max.	E Max.	T Max.	孔中心到板边缘的最小距离	安装下模沉孔直径 Max.
		螺母材料											
		碳钢	不锈钢										
	.112-40 (#4-40)	PL	PLC	440	.060	.060-.070	.234	.233	.215	.274	.130	.170	.132
	.138-32 (#6-32)	PL	PLC	632	.060	.060-.070	.265	.264	.246	.305	.130	.190	.158
	.164-32 (#8-32)	PL	PLC	832	.060	.060-.070	.297	.296	.278	.338	.155	.220	.184
	.190-32 (#10-32)	PL	PLC	032	.060	.060-.070	.312	.311	.293	.353	.165	.250	.210