



所有尺寸：毫米

公制螺纹	螺纹尺寸 x 螺距	规格型号			螺纹 代码	长度“L”±0.4 (长度单位为毫米)										最小 板厚	板开口 尺寸 +0.08	H ±0.4	S 最大值	孔中心到 板边缘的 最小距离
		钢碳	不 锈钢	铝 合金		6	8	10	12	15	18	-	-	-	-					
	M2.5x0.45	FH	FHS	FHA	M2.5	6	8	10	12	15	18	-	-	-	-	1.0	2.5	4.1	1.95	5.40
	M3x0.5	FH	FHS	FHA	M3	6	8	10	12	15	18	20	25	-	-	1.0	3.0	4.6	2.10	5.60
	M3.5x0.6	FH	FHS	FHA	M3.5	6	8	10	12	15	18	20	25	30	-	1.0	3.5	5.3	2.25	6.40
	M4x0.7	FH	FHS	FHA	M4	6	8	10	12	15	18	20	25	30	35	1.0	4.0	5.9	2.40	7.20
	M5x0.8	FH	FHS	FHA	M5	-	8	10	12	15	18	20	25	30	35	1.0	5.0	6.5	2.70	7.20
	M6x1.0	FH	FHS	FHA	M6	-	-	10	12	15	18	20	25	30	35	1.6	6.0	8.2	3.00	7.90
	M8x1.25	FH	FHS	FHA	M8	-	-	-	12	15	18	20	25	30	35	2.4	8.0	9.6	3.70	9.60

所有尺寸：英寸

英制螺纹	螺纹尺寸 x 螺距	规格型号			螺纹 代码	长度“L”±.015(长度=长度编码/16英寸)										最小 板厚	板开口 尺寸 +.003 -.000	H ±.015	S 最大值	孔中心到 板边缘的 最小距离
		碳 钢	不 锈钢	铝 合金		.250	.312	.375	.500	.625	.750	.875	1.00	1.25	1.50					
	.086-56 (#2-56)	FH	FHS	-	256	4	5	6	8	10	12	-	-	-	-	.040	.085	.144	.075	.187
	.112-40 (#4-40)	FH	FHS	FHA	440	4	5	6	8	10	12	14	16	20	-	.040	.111	.176	.085	.219
	.138-32 (#6-32)	FH	FHS	FHA	632	4	5	6	8	10	12	14	16	20	24	.040	.137	.206	.090	.250
	.164-32 (#8-32)	FH	FHS	FHA	832	4	5	6	8	10	12	14	16	20	24	.040	.163	.237	.090	.281
	.190-24 (#10-24)	FH	FHS	FHA	024	-	5	6	8	10	12	14	16	20	24	.040	.189	.256	.100	.281
	.190-32 (#10-32)	FH	FHS	FHA	032	-	5	6	8	10	12	14	16	20	24	.040	.189	.256	.100	.281
	.250-20 (1/4-20)	FH	FHS	FHA	0420	-	-	6	8	10	12	14	16	20	24	.062	.249	.337	.135	.312
	.313-18 (5/16-18)	FH	FHS	-	0518	-	-	-	8	10	12	14	16	20	24	.093	.311	.376	.160	.375